

## PRODUCT INFORMATION

# PRIMER C

## General Purpose Primer

### Description

Primer C is a moisture cure polyurethane primer suitable for use on many commonly encountered substrates such as concrete, paviors, bricks, timber and MDF.

### Uses

Primer C has been formulated principally as a primer for Colourplus, Coldgrip, Coldgrip BBA and Adtex. The low viscosity of Primer C permits deep penetration into dense surfaces, thereby ensuring a good bond. On friable substrates Primer C will serve to consolidate the surface, making it less porous and able to accept further coatings. Primer C confers outstanding flexibility and abrasion resistance and is well proven as a low cost concrete sealer and dustproofer for industrial floors.

### Benefits

- Excellent adhesion
- Low cost
- Good coverage
- Flexible
- Fast drying
- Easy to apply

Technical	
Specific Gravity	1.0-0.02
Covering Capacity	15 - 20 m <sup>2</sup> /litre
Flash Point	23 - 32°C
Application surface temp	1 - 40°C
Further coating Apply whilst still tacky usually after about 1 hour at 20°C, but within a maximum of 6 hours.	

### Colours

Light brown, transparent, low viscosity liquid.

### Surface Preparation

The surface must be clean, dry and free from any contamination including dirt, oil, grease, and curing agents on concrete. Particular attention should be given to ensuring the surface is free from moisture.

### Product Application

Application should be by brush or roller. Spraying is not recommended because of the health hazard in breathing atomised material (see Safety Data Sheet) and the difficulty of cleaning equipment. Clean equipment thoroughly before Primer C has cured. The prepared surface must be totally covered by a thin, even coating of Primer C. IN ORDER TO ENSURE GOOD ADHESION, IT IS ESSENTIAL THAT ANY FURTHER COATINGS ARE APPLIED WHILST PRIMER C IS STILL TACKY. If Primer C has been allowed to dry hard (after approx 24 hours), it will require thorough abrasion before further coatings can be applied. It is always advisable to try a test area before proceeding with the main application.

### Aftercare

None necessary.

### Packaging and Storage

Primer C is supplied in easy to handle 5 litre screw top rectangular tins. Primer C is highly flammable and should be stored tightly closed in a cool, dry, well-ventilated place. Keep away from sources of ignition. The shelf life is 1 year if tins are unopened.

### Health & Safety

Primer C is highly flammable. Keep away from sources of ignition. See Safety Data Sheet.

Published August 2015



**CompleteStreetsUSA**

*safe.smart.solutions*

866.367.3232 | [info@CompleteStreetsUSA.com](mailto:info@CompleteStreetsUSA.com)